



## LOAD CERTIFICATE: 6.50-16

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 8

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
6.50-16	4.50E	175 6.9	760 30.0	356 14.0	2274 89.5	8 PR 94 A8	3.2	1710	1140	790	730	630	570
							46	3770	2510	1740	1610	1390	1260
							3.5	1800	1200	830	770	670	600
							51	3960	2640	1830	1700	1480	1320
							3.8	1890	1260	870	810	700	630
							55	4160	2780	1920	1780	1540	1390
							<b>4.2</b>	<b>2010</b>	<b>1340</b>	<b>920</b>	<b>860</b>	<b>740</b>	<b>670</b>
							<b>61</b>	<b>4430</b>	<b>2950</b>	<b>2030</b>	<b>1890</b>	<b>1630</b>	<b>1480</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification