



LOAD CERTIFICATE: 6.50-20

Brand: ASCENSO

Tread Pattern : TSB 111

Ply Rating: 8

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code : F-2



Salient Features

Unique Dumbbell Pattern:

Reduces block tearing & shoulder block deformation

Strong Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
6.50-20	4.50F	175 6.8	865 34.0	397 15.6	2588 101.8	8 PR 93 A8	2.9	1650	1100	760	700	610	550
							42	3630	2420	1670	1540	1340	1210
							3.2	1740	1160	800	740	640	580
							46	3830	2560	1760	1630	1410	1280
							3.5	1830	1220	840	780	680	610
							51	4030	2690	1850	1720	1500	1340
							3.85	1950	1300	900	830	720	650
							56	4300	2860	1980	1830	1590	1430

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com