



## LOAD CERTIFICATE: 7.50-18

**Release Month:** December'20

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 8

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
7.50-18	5.50F	203 7.9	859 33.8	395 15.5	2570 101.2	8 PR 102 A8	2.9	2160	1440	990	920	800	720
							42	4760	3170	2180	2030	1760	1590
							3.2	2280	1520	1050	970	840	760
							46	5020	3350	2310	2140	1850	1670
							3.5	2400	1600	1110	1020	890	800
							51	5290	3520	2420	2250	1960	1760
							<b>3.85</b>	<b>2550</b>	<b>1700</b>	<b>1170</b>	<b>1090</b>	<b>940</b>	<b>850</b>
							<b>56</b>	<b>5620</b>	<b>3740</b>	<b>2580</b>	<b>2400</b>	<b>2070</b>	<b>1870</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification