



## LOAD CERTIFICATE: 7.50-20

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 8

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
7.50-20	5.50F	205 8.0	915 36.0	420 16.5	2719 107.0	8 PR 105 A8	2.9	2340	1560	1080	1000	870	780
							42	5150	3440	2380	2200	1920	1720
							3.2	2490	1660	1150	1060	920	830
							46	5480	3660	2530	2330	2030	1830
							3.5	2610	1740	1200	1110	970	870
							51	5750	3830	2640	2440	2140	1920
							<b>3.85</b>	<b>2780</b>	<b>1850</b>	<b>1280</b>	<b>1180</b>	<b>1030</b>	<b>925</b>
							<b>56</b>	<b>6120</b>	<b>4070</b>	<b>2820</b>	<b>2600</b>	<b>2270</b>	<b>2040</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)