



LOAD CERTIFICATES: 10.0/75-15.3

Brand: ASCENSO

Tread Pattern : MPB 400

Tyre Construction: Bias

Ply Rating: 18

Type: Tube Less

Main Applications: Telehandlers, Compact wheel loader, and implement machinery.

TRA Code : R-4



Salient Features

Specially designed for Multipurpose Applications:

- Wider Centre Lug for Comfort & Smooth Ride.
- Designed for Better Grip & Traction.
- Increased carcass strength for Durability.



Technical Specification

Size	Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR / Load Index / Speed Index	Inflation Pressure	Recommended load, kg							
								Speed, km/h							
		SW	OD	mm	mm	bar	Mixed application				Drive Wheel				
		mm	mm				Free rolling		Drive Wheel		Drive Wheel				
		in	in				10	25	40	50	10	25	40	50	
psi	6	16	25	31	6	16	25	31							
10.0/75-15.3 (ECE106)	9	264	760	348	2274	18	7.1	3050	2590	2180	1960	2170	1840	1550	1400
		10.4	29.9	13.7	89.5	135A8 FR 123A8 DW									

Note:All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover