



LOAD CERTIFICATES: 11.5/80-15.3

Brand: ASCENSO

Tread Pattern : MPB 400

Tyre Construction: Bias

Ply Rating: 18

Type: Tube Less

Main Applications: Telehandlers, Compact wheel loader, and implement machinery.

TRA Code : R-4



Salient Features

Specially designed for Multipurpose Applications:

- Wider Centre Lug for Comfort & Smooth Ride.
- Designed for Better Grip & Traction.
- Increased carcass strength for Durability.



Technical Specification

Size	Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR / Load Index / Speed Index	Inflation Pressure	Recommended load, kg							
								Speed, km/h							
		Mixed application													
		Free rolling				Drive Wheel									
		bar	10	25	40	50		10	25	40	50				
psi	6	16	25	31	6	16	25	31							
11.5/80-15.3 (ECE106)	9	290	845	383	2528	18	6.0	3820	3240	2725	2450	2660	2260	1900	1710
		11.4	33.3	15.1	99.5	143A8 FR 130A8 DW		87	8400	7130	6000	5390	5850	4970	4180

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com