



LOAD CERTIFICATES: 12.5-20

Brand: ASCENSO

Tread Pattern : MPB 400

Tyre Construction: Bias

Ply Rating: 12

Type: Tube Less

Main Applications: Telehandlers, Compact wheel loader, and implement machinery.

TRA Code : R-4



Salient Features

Specially designed for Multipurpose Applications:

- Wider Centre Lug for Comfort & Smooth Ride.
- Designed for Better Grip & Traction.
- Increased carcass strength for Durability.



Technical Specification

Size	Rim	Unloaded Dimensions		Static Load Radius	Rolling Circumference	PR / Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
		mm	mm	mm	mm	Mixed application										
		in	in	in	in	bar	15	20	30	40	50	60	70	80	90	
						psi	9	12	19	25	31	37	43	50	56	
12.5-20 (ECE54)	11	325	1040	473	3110	12PR	3.5	3300	3000	2500	2300	2240	2200	2140	2080	2000
		12.8	40.9	18.6	122.4	132 G	51	7270	6610	5510	5070	4930	4850	4710	4580	4410

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover