



SPB 260

Product Data Sheet

Marketing Department.

Oct 06, 2022

This document is created to register the marketing communication collaterals and process details for the launch of the above-mentioned pattern; it is intended for internal circulation and approval for further dissemination. All facts and figures mentioned in the document is true to the best of our knowledge as on the above said date, for updated information please feel free to visit the website www.ascensotyres.com

Release Month: Oct '22

Brand: ASCENSO

Tread Pattern : SPB 260

Tyre Construction : Bias

Type : Tubeless

Main Applications: Sugarcane Trailer
And Compactor

TRA Code : R-3

List of Sizes

Size	PR
23.1-26	18
620/75-30 (23.1-30)	16
650/75-32 (24.5-32)	16



Salient Features

Large Tread Area:

- Increases flotation and minimises ground disturbance in soil

Optimized Diamond Lug Pattern with Sipes:

- Reduces groove cracks and minimises slippage, enhances productivity

Heavy Under Thread:

- Ensures puncture and impact resistance, thereby reducing downtime



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / Load Index / Speed Index	Inflation Pressure	Recommend load (kg)
		SW	OD					Speed (kmph)
		mm	mm					40
		inch	inch	inch	inch		psi	25
23.1-26	DW20B	587	1581	710	4748	18PR	2.6	6000
		23.1	62.2	27.9	186.9	170 A8	38	13220

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR / Load Index / Speed Index	Inflation Pressure	Recommend load (kg)
		SW	OD					Speed (kmph)
		mm	mm					30
		inch	inch	inch	inch		psi	19
620/75-30 (23.1-30)	DW20A	605	1675	758	5010	16PR	2.3	4625
	DW20B	23.8	65.9	29.8	197.2	161 A6	33	10190
650/75-32 (24.5-32)	DH21	625	1755	795	5249	16PR	2.1	5000
	DH21B	24.6	69.1	31	207	164 A6	30	11010

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover