

PRODUCT DATA SHEET

SPR 250

Tyre Construction: Radial

Type: Tube Less

Main Applications: Small Tractors, Implements

TRA Code: IMP



Salient Features:

- Uniquely designed to **protect fields/ grasslands and provide rapid self-cleaning.**
- **Excellent forward and reverse traction on inclined surfaces.**
- **Enhanced vehicle stability and manoeuvrability** on account of improved sidewall stiffness.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm	mm	mm	mm		bar	50	
		inch	inch	inch	inch		psi	31	
31X15.50R15	13LB	391	792	360	2369	122 B	2.8	1500	
		15.4	31.2	14.2	93.3		41	3300	
33X15.50R15	13LB	391	843	381	2521	126 B	3.2	1700	
		15.4	33.2	15.0	99.3		46	3740	

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm	mm	mm	mm		Mixed application								
		inch	inch	inch	inch		bar	Static	10	25	30	40	50	65	
440/50R17 (SB)	13	441	872	397	2608	135 D	2	3150	2470	2160	2070	1860	1660	1370	
							29	6940	5440	4760	4560	4100	3660	3020	
							2.4	3630	2840	2500	2390	2150	1910	1580	
							35	8000	6260	5510	5260	4740	4210	3480	
							2.8	4120	3220	2830	2700	2430	2170	1790	
		41	9070	7090	6230		5950	5350	4780	3940					
		3.2	4530	3550	3110		2970	2680	2380	1970					
		46	9980	7820	6850		6540	5900	5240	4340					
		3.6	4970	3890	3410		3260	2940	2610	2160					
		52	10950	8570	7510		7180	6480	5750	4760					
480/45R17 (SB)	16	477	858	392	2566	137 D	2.4	3750	2930	2580	2460	2220	1970	1630	
							35	8260	6450	5680	5420	4890	4340	3590	
							2.8	4260	3330	2920	2790	2520	2240	1850	
							41	9380	7330	6430	6150	5550	4930	4070	
							3.2	4670	3650	3210	3070	2760	2460	2030	
		46	10290	8040	7070		6760	6080	5420	4470					
		3.6	5130	4010	3520		3370	3030	2700	2230					
		52	11300	8830	7750		7420	6670	5950	4910					
		4	5290	4140	3630		3470	3130	2780	2300					
		58	11650	9120	8000		7640	6890	6120	5070					

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 • E: enquiry@ascensotyres.com • W: www.ascensotyres.com



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI&SI	Inflation Pressure	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm	mm	mm	mm		Mixed application								
		inch	inch	inch	inch		bar	Static	10	25	30	40	50	65	
						psi		6	16	19	25	31	40		
500/50R17 (SB)	16	503	932	422	2787	147 D	2.8	5040	3940	3460	3310	2980	2650	2190	
							41	11100	8680	7620	7290	6560	5840	4820	
							3.2	5540	4340	3810	3640	3280	2920	2410	
							46	12200	9560	8390	8020	7220	6430	5310	
							3.6	6070	4750	4170	3990	3590	3190	2640	
	19.8	36.7	16.6	109.7	52		13370	10460	9190	8790	7910	7030	5810		
					4		6670	5220	4580	4380	3940	3510	2900		
					58		14690	11500	10090	9650	8680	7730	6390		
					4.4		7070	5540	4860	4640	4180	3720	3075		
					64		15570	12200	10700	10220	9210	8190	6770		

Note: SB - Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

