



# LOAD CERTIFICATE: 440/65R28

**Brand:** ASCENSO

**Tread Pattern :** TDR 650

**Tyre Construction:** Radial

**LSI :** 138 D

**Type:** Tube Less

**Main Applications:** 4WD Tractor

**TRA Code :** R-1W



## Salient Features

### **Optimum Tread Design:**

Maximum performance in field and on road operations

### **First in the Industry with Dual Mud Breakers:**

Ensure better self-cleaning

### **Greater Lug Overlap:**

Provides safe and comfortable ride at high speeds



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm	mm					Mixed application						
		in	in					mm	mm	in	in	Bar	Psi	Static
440/65 R28	W14L	441 17.3	1283 50.5	591 23.2	3837 151	138 D	1.6	4490	2930	2310	2240	2140	2050	1950
							23	9890	6450	5090	4930	4710	4520	4300
							1.8	4740	3090	2440	2370	2260	2160	2060
							26	10440	6810	5370	5220	4980	4760	4540
							2.0	4990	3260	2570	2500	2380	2280	2170
							29	10990	7180	5660	5510	5240	5020	4780
							2.2	5200	3390	2680	2600	2470	2370	2260
							32	11450	7470	5900	5730	5440	5220	4980
							2.4	5430	3540	2800	2710	2580	2480	2360
							35	11960	7800	6170	5970	5680	5460	5200

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)