



LOAD CERTIFICATES: 13.00-24

Brand: ASCENSO

Tread Pattern : MIB 406

Tyre Construction: Bias

Ply Rating: 14

Type: Tube Less

Main Applications: Compact Wheel loaders, backhoe loaders,
Telescopic Handler and Grader

TRA Code : L2/G2



Salient Features

Robust Solid Centre Block Pattern:

- Provides Maximum Ground Contact.
- Ensures Even Load Distribution.
- Suitable for Rugged Terrains.
- The Open Shoulder Lug Pattern Provides Excellent Traction.



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI OR PR	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm					mm	mm	bar	10	40
		in	in					in	in	psi	7	25
13.00-24	10	353	1278	581	3822	14 PR 170 A2	5.25	6000	3000			
		13.9	50.3	22.9	150.5		77	13200	6600			

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com