



LOAD CERTIFICATES: 335/80R20 (SB)

Brand: ASCENSO

Tread Pattern : CLR 280

Tyre Construction: Radial

LSI : 136 B/147 A2

Type: Tubeless

Main Applications: Compact Loader

TRA Code : IND



Salient Features

- CLR 280 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications.
- Wide non-directional tread design offers outstanding traction, control & handling stability on any surface, including industrial application on the harder surfaces.
- Steel belt package for enhanced resistance to penetration and durability.
- High Load-bearing capacity is ensured by robust carcass and a strong bead.
- Special Tread compound offers superior resistance to cuts & chips increased fuel efficiency, reduced heat build-up resulting in a longer service life.
- Large centre tread blocks contribute to a smoother, more comfortable ride.



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm					Mixed application				
		in	in					10	20	30	40	50
						Bar	Psi	6	12	19	25	31
335/80R20 (SB)	11	339 13.3	1044 41.1	475 18.7	3135 123.4	136 B/147 A2	2.0	1870	1500	1440	1400	1360
							29	4120	3300	3170	3080	3000
							2.5	2220	1780	1720	1670	1620
							36	4890	3920	3790	3680	3570
							3.0	2580	2070	1990	1940	1880
							44	5680	4560	4380	4270	4140
							3.5	2940	2350	2270	2200	2140
							51	6480	5180	5000	4850	4710
							3.75	3075	2460	2370	2310	2240
							54	6770	5420	5220	5090	4930

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited,
 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013,
 India

T: +91 22 4348 1600 Website: www.ascensotyres.com