



LOAD CERTIFICATES: 365/70R18 (SB)

Brand: ASCENSO

Tread Pattern : CLR 280

Tyre Construction: Radial

LSI : 135 B/146 A2

Type: Tubeless

Main Applications: Compact Loader

TRA Code : IND



Salient Features

- CLR 280 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications.
- Wide non-directional tread design offers outstanding traction, control & handling stability on any surface, including industrial application on the harder surfaces.
- Steel belt package for enhanced resistance to penetration and durability.
- High Load-bearing capacity is ensured by robust carcass and a strong bead.
- Special Tread compound offers superior resistance to cuts & chips increased fuel efficiency, reduced heat build-up resulting in a longer service life.
- Large centre tread blocks contribute to a smoother, more comfortable ride.



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm					Mixed application				
		in	in					10	20	30	40	50
						Bar	Psi					
365/70R18 (SB)	11	360 14.1	969 38.1	440 17.3	2910 114.5	135 B/146 A2	2.0	1800	1440	1390	1350	1310
							29	3960	3170	3060	2970	2890
							2.5	2150	1720	1650	1610	1560
							36	4740	3790	3630	3550	3440
							3.0	2490	1990	1920	1860	1810
							44	5480	4380	4230	4100	3990
							3.5	2830	2270	2180	2120	2060
							51	6230	5000	4800	4670	4540
							3.75	3000	2400	2310	2250	2180
							54	6610	5290	5090	4960	4800

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited,
 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013,
 India

T: +91 22 4348 1600 Website: www.ascensotyres.com