



LOAD CERTIFICATES: 405/70R20 (SB)

Brand: ASCENSO

Tread Pattern : CLR 280

Tyre Construction: Radial

LSI : 143 B/155 A2

Type: Tubeless

Main Applications: Compact Loader

TRA Code : IND



Salient Features

- CLR 280 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications.
- Wide non-directional tread design offers outstanding traction, control & handling stability on any surface, including industrial application on the harder surfaces.
- Steel belt package for enhanced resistance to penetration and durability.
- High Load-bearing capacity is ensured by robust carcass and a strong bead.
- Special Tread compound offers superior resistance to cuts & chips increased fuel efficiency, reduced heat build-up resulting in a longer service life.
- Large centre tread blocks contribute to a smoother, more comfortable ride.



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm					Mixed application				
		in	in					10	20	30	40	50
						Bar	Psi	6	12	19	25	31
405/70R20 (SB)	13	407 16	1076 42.3	488 19.2	3231 127.2	143 B/155 A2	2.0	2320	1790	1730	1680	1630
							29	5110	3940	3810	3700	3590
							2.5	2760	2130	2060	2000	1940
							36	6080	4690	4540	4410	4270
							3.0	3200	2480	2390	2320	2250
							44	7050	5460	5260	5110	4960
							3.5	3640	2820	2710	2640	2560
							51	8020	6210	5970	5810	5640
							3.75	3875	3000	2890	2810	2725
							54	8540	6610	6370	6190	6000

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited,
 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013,
 India

T: +91 22 4348 1600 Website: www.ascensotyres.com