



## LOAD CERTIFICATES: 650/55R26.5 (SB)

---

**Brand:** ASCENSO

**Tread Pattern :** FTR 170

**Tyre Construction:** Radial

**LSI :** 178 D

**Type:** Tube Less

**Main Applications:** Implements, Trailers, Slurry Tankers and  
Dump Trailer

**TRA Code :** IMP



## Salient Features

### Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)						
		Speed, km/h (mph)												
		Mixed application												
		bar	Static					10	25	30	40	50	65	
psi		6	16	19	25	31	40							
mm	mm	mm	mm	mm	mm	mm	mm							
in	in	in	in	in	in	in	in							
650/55R26.5 (SB)	AG20.00	645 25.4	1389 54.7	632 24.9	4171 164.2	178 D	3.2	11040	8640	7580	7250	6530	5810	4800
							46	24320	19030	16700	15970	14380	12800	10570
							3.6	12120	9490	8330	7960	7170	6380	5270
							52	26700	20900	18350	17530	15790	14050	11610
							4.0	13270	10390	9120	8710	7850	6980	5770
							58	29230	22890	20090	19190	17290	15370	12710
							5.0	14930	11680	10250	9800	8830	7850	6490
							73	32890	25730	22580	21590	19450	17290	14300
							6	17250	13500	11850	11330	10200	9080	7500
87	38000	29740	26100	24960	22470	20000	16520							

**Note:** All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited,  
 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013,  
 India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)