

PRODUCT DATA SHEET

BLB 730

Tyre Construction: Bias

Type: Tube Less

Main Applications: Boom Lift

TRA Code: NHS



Salient Features:

Reinforced lug design with longer shoulder:

Ensures excellent traction & Stability.

Rim Guard Protector with Extra Heavy-Duty Sidewall:

Safeguards the tire against damage.

Extra Strong Casing:

Higher load-carrying capacity in all applications & Improved Stability.

Special Rubber compound:

Longer Tire Life-reduced downtime and higher productivity.

Optimized inner volume:

- For low tire fill consumption
- To be filled with foam to eliminate chances of flat.



Technical Data



Size	Rec. Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR & LI/SI	Infl. Pressure	Recommended Load (kg) (lbs)		
		SW	OD					Speed (kmph) (mph)		
		mm	mm				mm	mm	bar	10
		Inch	Inch				Inch	Inch	psi	6
26x12D380	10	308	665	308	1997	8PR 120 A2	2.9	1400		
		12.1	26.2	12.1	78.6		42	3080		
15-625	15	388	1035	481	3108	16 PR 168 A2	6.9	5600		
		15.3	40.7	19	122.4		100	12350		
18-625	15	436	1028	479	3087	16 PR 175 A2	6.9	6900		
		17.2	40.5	18.8	121.5		100	15210		
IN 315/55D20	11	321	828	386	2486	12 PR 151 A2	5.5	3450		
		12.6	32.6	15.2	97.9		80	7610		
IN 355/55D625	11.75	351	938	441	2817	14 PR 157 A2	5.2	4125		
		13.8	36.9	17.4	110.9		75	9090		
385/65D22.5 (15.5-22.5)	11.75	395	1090	500	3273	16PR 168 A2	6.9	5600		
		15.6	42.9	19.7	128.9		100	12320		
445/65D22.5 (18-22.5)	14	450	1170	533	3513	18PR 177 A2	6.9	7300		
		17.7	46.1	21	138.3		100	16060		
IN 445/50D710	15	435	1185	551	3558	18 PR 177 A2	6.9	7300		
		17.1	46.7	21.7	140.1		100	16090		

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com