

# PRODUCT DATA SHEET

## ***BOSS PN 40***

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** Pick & Carry Crane

**TRA Code:** NA



### ***Salient Features:***

**Tread Design Multiple Ribs:**

- Provides excellent Manoeuvrability.
- Better Roadability.

**Robust Carcass:**

- Better load carrying capacity.

**Reinforced Sidewall:**

- Ensures stability in loaded and unloaded conditions.

**Optimized Tread Compound:**

- Ensures longer tire life.
- Resistant to cuts and chips.



# Technical Data



Tyre Size	PR	TT/TL	LI/SI	Recomm. Rim	Alt. Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity	
						SW	OD				Inflation Pressure	Max Load
						mm	mm					
						inch	inch					
11.00-20	16	TT	155B	8.0	8.5	290	1085	492	3245	50	7.8	3875
						11.4	42.7	19.4	127.8	31	112	8540
11.00-20	18	TT	157B	8.0	8.5	290	1085	492	3245	50	8.6	4125
						11.4	42.7	19.4	127.8	31	125	9095

**Note:** All tyres confirm to ETRTO standards

## Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)