

# PRODUCT DATA SHEET

## **BHB 311**

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Backhoe Loader

**TRA Code:** IND



### ***Salient Features:***

**Robust Lug Design:**

Combination of robust lugs used in industrial applications and good self-cleaning properties.

**Flat & Wider Tread:**

Excellent stability during vehicle operation

**Special Tread Compound:**

Ensures longer tyre life



# Technical Data



Size	Rim	Unloaded Dimensions		Loaded	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load, kg (lbs)			
				Static				Speed, km/h (mph)			
		SW	OD	Radius	Agricultural Use-Field		Agricultural Use-Road Transport				
		mm	mm	mm			10	20	30	40	
in	in	in	in	6	12	19	25				
18.4-26	16	467	1450	656	4337	12PR 156 A8	2.5	5000	4360	4160	4000
		18.39	57.09	25.83	170.75		36	11010	9600	9160	8810

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

