

# PRODUCT DATA SHEET

## **BHB 312**

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Backhoe Loader

**TRA Code:** IND



### ***Salient Features:***

**Robust Lug Design:**

Combination of robust lugs used in industrial applications and good self-cleaning properties.

**Flat & Wider Tread:**

Excellent stability during vehicle operation

**Special Tread Compound:**

Ensures longer tyre life



# Technical Data



Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm	mm				mm	mm	Bar	40
		in	in				in	in	Psi	25
19.5L-24	DW16L	495	1314	596	3930	12PR	2.3	3450		
		19.5	51.7	23.5	154.7	151 A8	34	7600		
21L-24	DW18L	533	1378	622	4122	12PR	2.2	3875		
		21.0	54.3	24.5	162.3	155 A8	32	8540		
21.3/70-24	DW18L	533	1378	622	4122	16PR	2.8	4500		
		21.0	54.3	24.5	162.3	160 A8	41	9920		

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

