

# PRODUCT DATA SHEET

## **BHB 315**

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Backhoe Loader

**TRA Code:** IND



### ***Salient Features:***

**Unique Tread Design:**

- Wide & sturdy center block gives high contact area and better stability.
- High solid to void ratio gives long service life.
- Superior compound provides the ability to work in tough construction applications.



# Technical Data



| Size       | Rim  | Unloaded Dimension |       | Loaded | Rolling Circumference | PR & LSI       | Recommended Load | Inflation Pressure | Speed |
|------------|------|--------------------|-------|--------|-----------------------|----------------|------------------|--------------------|-------|
|            |      | SW                 | OD    | Static |                       |                |                  |                    |       |
|            |      |                    |       | Radius |                       |                |                  |                    |       |
|            |      |                    |       | mm     |                       |                |                  |                    |       |
| in         | mm   | in                 | mm    | in     | Kg                    | bar            | Km/h             |                    |       |
| in         | in   | in                 | in    | in     | lbs                   | psi            | mph              |                    |       |
| 12.5/80-18 | W9   | 308                | 965   | 438    | 2886                  | 14PR<br>132 A8 | 2000             | 4.3                | 40    |
|            |      | 12.13              | 37.99 | 17.24  | 113.62                |                | 4410             | 62                 | 25    |
| 19.5L-24   | W16L | 495                | 1314  | 595    | 3930                  | 14PR<br>154 A8 | 3750             | 2.6                | 40    |
|            |      | 19.5               | 51.7  | 23.4   | 154.7                 |                | 8260             | 38                 | 25    |
| 18.4-26    | W16L | 467                | 1426  | 646    | 4265                  | 14PR<br>160 A8 | 4500             | 2.9                | 40    |
|            |      | 18.4               | 56.1  | 25.4   | 167.9                 |                | 9910             | 42                 | 25    |
| 16.9-28    | W15L | 429                | 1410  | 644    | 4217                  | 14PR<br>156 A8 | 4000             | 3.2                | 40    |
|            |      | 16.9               | 55.5  | 25.4   | 166.0                 |                | 8810             | 46                 | 25    |

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

