

PRODUCT DATA SHEET

BOSS BH 33

Tyre Construction: Bias

Type: Tube Type

Main Applications: Backhoe Loader

TRA Code: IND



Salient Features:

Unique Tread pattern Design:

Provides Improved traction under heavy-duty service conditions.

Circumferential Grooves with Transverse slots at shoulder region:

Free Rolling characteristics & Minimizes Side slippage while in operation.

Strong Nylon Casing:

High load carrying capacity.

Specially designed CCR Compound:

Cut and chip-resistant compound provides excellent resistance to severe terrain conditions.



Technical Data



Tyre Size	PR	LI/SI	Recomm. Rim	Alternate Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity	
					SW	OD				Inflation Pressure	Max Load
					mm	mm				bar	kg
					inch	inch				psi	lbs
9.00-16	16	149 A8	6.50H	6.00G	248	912	412	2728	40	8.5	3230
					9.8	35.9	16.2	107.4	25	123	7110

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com