

# PRODUCT DATA SHEET

## EXB 380

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** Excavator

**TRA Code:** R-3



### *Salient Features:*

**Optimized Lug Angle**

Excellent traction & self-cleaning properties.

**Wider Tread Pattern:**

Provides excellent stability during vehicle operation.

**Strong Nylon Casing:**

Enhanced load carrying capacity.



# Technical Data



Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
		mm	mm					Static	5	10	20	25	30	40	45	50	
		Inch	Inch						3	6	12	16	19	25	28	31	
8.25-20	6.5	230	962	442	2878	14 PR	6.8	4120	2880	2410	2330	2290	2270	2180	2100	2060	
		9.1	37.9	17.4	113.3	133 B	98	9070	6340	5310	5130	5040	5000	4800	4630	4540	
9.00-20	7	258	1018	465	3045	14PR	7.0	5000	3500	2930	2830	2780	2750	2650	2550	2500	
		10.2	40.1	18.3	119.9	140 B	102	11010	7710	6450	6230	6120	6060	5840	5620	5510	
10.00-20	7.5	275	1052	479	3147	16PR	7.5	6000	4200	3510	3390	3330	3300	3180	3060	3000	
		10.8	41.4	18.9	123.9	146 B	109	13220	9250	7730	7470	7330	7270	7000	6740	6610	
11.00-20	8	286	1082	491	3237	16PR	7.2	6500	4550	3800	3670	3610	3580	3450	3320	3250	
		11.3	42.6	19.3	127.4	149 B	104	14320	10020	8370	8080	7950	7890	7600	7310	7160	

**Note: All tyres confirm to ETRTO standards**

**Mahansaria Tyres Pvt. Ltd.**

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

