

PRODUCT DATA SHEET

MIB 406

Tyre Construction: Bias

Type: Tube Less

Main Applications: Backhoe Loader, Telehandler,
Grader, Wheel Loader

TRA Code: L-2/G-2



Salient Features:

Robust Solid Center Block pattern:

- Provides maximum ground contact.
- Ensures even load distribution.
- Suitable for rugged terrains
- The open shoulder lug pattern provides excellent traction.



Technical Data



| Size | Rim | Unloaded Dimension | | Loaded | Rolling Circumference | PR & LI/SI | Recommended Load | Inflation Pressure | Speed |
|----------|-----|--------------------|------|--------|-----------------------|-----------------|------------------|--------------------|-------|
| | | | | Static | | | | | |
| | | SW | OD | Radius | mm | | Kg | bar | Km/h |
| | | mm | mm | mm | mm | | lbs | psi | mph |
| 13.00-24 | 10 | 353 | 1278 | 581 | 3822 | 14 PR 170 A2 | 3000 | 3.25 | 40 |
| | | | | 6600 | 48 | | 25 | | |
| | | 13.9 | 50.3 | 22.9 | 150.5 | | 6000 | 5.25 | 10 |
| | | | | 13200 | 77 | | 7 | | |
| 14.00-24 | 10 | 377 | 1348 | 610 | 4032 | 16 PR 177 A2 | 3650 | 3.5 | 40 |
| | | | | 8030 | 51 | | 25 | | |
| | | 14.8 | 53.1 | 24.0 | 158.7 | | 7300 | 5.5 | 10 |
| | | | | 16060 | 80 | | 7 | | |
| 15.5-25 | 13 | 404 | 1278 | 583 | 3822 | 12 PR 168 A2 | 2650 | 2.5 | 40 |
| | | | | 5830 | 37 | | 25 | | |
| | | 15.9 | 50.3 | 23.0 | 150.5 | | 5600 | 4 | 10 |
| | | | | 12320 | 59 | | 7 | | |
| 17.5-25 | 14 | 445 | 1346 | 611 | 4026 | 16 PR 177 A2 | 3350 | 2.75 | 40 |
| | | | | 7370 | 40 | | 25 | | |
| | | 17.5 | 53.0 | 24.1 | 158.5 | | 7300 | 4.75 | 10 |
| | | | | 16060 | 69 | | 7 | | |

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

