

PRODUCT DATA SHEET

MIB 407

Tyre Construction: Bias

Type: Tube Less

Main Applications: Backhoe Loader,
Compact Wheel Loader

TRA Code: IND



Salient Features:

Tread Design:

- Extra thick sidewall
- Ensure puncture resistance.
- Side walls allow stability.

Enhance Carcass Construction:

Ensures high load carrying capacity.



Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommended load, kg (lbs)					
				Static				Speed (kmph) (mph)					
		SW	OD	Radius				Mixed Application					
		mm	mm	mm				mm	Bar	Static	10	25	30
inch	inch	inch	inch	PSI	6	16	19	25					
400/80-24	DW13	414	1250	569	3738	20PR 162 A8	5	10930	5940	5040	4940	4750	
		16.3	49.2	22.4	147.2		73	24100	13100	11110	10890	10470	
440/80-24	DW14L	451	1314	595	3930	22PR 168 A8	5	12880	7000	5940	5820	5600	
		17.8	51.7	23.4	154.7		73	28400	15430	13100	12830	12350	

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

