

PRODUCT DATA SHEET

PEB 721

Tyre Construction: Bias

Type: Tube Less/ Tube Type

Main Applications: Reach Stacker

TRA Code: IND-4



Salient Features:

High Rubber Distribution provides:
Higher traction and better load-carrying capacity.

Optimized Tread Design:
Quick heat dissipation and cooler running on hard concrete surfaces.

Specially Formulated Tread Compound:
Better Mileage and a Longer tire life,
Resistant to cuts & snags with optimized wear.

Strong Casing/Carcass:
Used in Heavy duty applications, & it ensures maximum operating efficiency and exceptional stability in lift mode.



Technical Data



Size	Tyre Type	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)			
			SW	OD					Speed (kmph) (mph)			
			mm	mm				mm	mm	Bar	10	25
			inch	inch				inch	inch	psi	6	16
12.00-24	TT	8.5	315	1265	575	3783	20	9.9	9320	8630		
			12.4	49.8	22.6	149		144	20550	19030		
12.00-24	TT	8.5	315	1265	575	3783	24	10	10270	9510		
			12.4	49.8	22.6	149		145	22560	20970		
18.00-25	TL	13.00/2.5	528	1675	747	5010	40	10.3	22950	21250		
			20.8	65.9	29.4	197.2		150	50600	46860		

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

