

PRODUCT DATA SHEET

SSB 332

Tyre Construction: Bias

Type: Tube Less

Main Applications: Skid Steer

TRA Code: NHS (L-5)



Salient Features:

Extra Deep Tread Depth:

Superior traction and long life

Wider & Sturdier Blocks:

High stability and puncture resistance

Advanced Tread Compound:

Excellent wear resistance in severe conditions.



Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LI/SI	Recommended Load	Inflation Pressure	Speed
		SW	OD	Static					
		mm	mm	Radius					
		in	in	mm					
				mm			Kg	bar	Km/h
				in			lbs	psi	mph
10-16.5	8.25	264	773	356	2312	10PR 134 A2	2120	5.2	10
							4675	75	6
12-16.5	9.75	307	831	380	2486	12PR 145 A2	2900	5.5	10
							6390	80	6

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

