

# PRODUCT DATA SHEET

## SSB 333

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Skid Steer

**TRA Code:** NHS



### *Salient Features:*

**High tread depth, broad lugs and special compound:**

Makes it optimal for usage on hard & rough surfaces.

**Robust Casing:**

Highly provides durability with protection against  
Punctures & damages

**Rim Guard:**

Protect the rim flange area against flats and wheel damages.



# Technical Data



Size	Rim	Unloaded Dimension		Loaded	Rolling Circumference	PR & LI/SI	Recommended Load	Inflation Pressure	Speed
		SW	OD	Static					
				Radius					
		mm	mm	mm	mm				
in	in	in	in						
10-16.5	8.25	264	773	356	2312	10PR	2120	5.2	10
		10.4	30.4	14.0	91.0	134 A2	4670	75	6
12-16.5	9.75	318	835	381	2497	12PR	2900	5.5	10
		12.5	32.9	15.0	98.3	145 A2	6390	80	6

**Note: All tyres confirm to ETRTO standards**

## Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: [www.ascensotyres.com](http://www.ascensotyres.com)

