

PRODUCT DATA SHEET

BOSS TD 16

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tractor

TRA Code: R-1



Salient Features:

Dual-Lug Angle Design with High inner volume:

- Excellent Self-Cleaning Properties.
- Excellent Traction.

Centre Tie bar with Strong Lug Base:

- Minimizes lug shuffling in operation.

Superior Nylon Construction:

- High load carrying capacity.

Deep Tread:

- Improved Mileage.
- Enhanced Performance in both Field and Haulage

CCR (Cut & Chip Resistance) Compound:

- Resistance to Cut & Chip & also minimizes Puncture.



Technical Data



Tyre Size	PR	TT/TL	LI/SI	Recomm. Rim	Unloaded Inflated Dimension		Static Loaded Radius	Rolling Circumference	Max Speed	Load Carrying Capacity	
					SW	OD				Inflation Pressure	Max. Load
					mm	mm					
					inch	inch					
9.5-24	12	TT	114 A6	W8	245	1065	492	3185	30	3.0	1180
					9.6	41.9	19.4	125.4	19	43	2595
13.6-28	12	TT	128 A6	W12	360	1340	603	3918	30	2.3	1800
					14.2	52.8	23.7	154.2	19	33	3960
14.9-28	12	TT	134 A6	W13	388	1380	625	4082	30	2.3	2120
					15.3	54.3	24.6	160.7	19	33	4670
16.9-28	12	TT	143 A6	W15L	436	1450	660	4336	30	2.4	2725
					17.2	57.1	26.0	170.7	19	35	5995

Note: All tyres confirm to ETRTO standards.

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com