

PRODUCT DATA SHEET

VDR 2000

Tyre Construction: Radial

Type: Tubeless

Main Applications: Tractor

TRA Code: R-1W



Salient Features:

Advanced Tread design with Wider & longer footprint:

- More Gripping Edge.
- Excellent Traction with minimum amount of slip.
- Reduce Soil stress, Compaction & improved yields.
- More no of lugs acting together at same time, deliver more tractive force.

Overlap of lugs:

- Leads to a comfortable and smooth drive on road.

Extra Strong Casing with High Performance Steel belts:

- Radially stiffer carcass, enough to absorb impact and stress and returns its original shape. It ensures long term robustness & comfort ride.
- SB offers better impact resistance and defends against stubble to enhance tire more durable.

SSR compound (Special Stubble Resistant):

- Longer Tire Life and defense against stubble which provides better protection on field.



Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm					10	25	30	40	50	65	70
				inch	inch					6	16	19	25	31	40	43
VF 600/60R28 NRO (SB)	DW20B	DW21B	DW18L	597	1431	653	4297	160D	0.6	2460	2310	2280	2240	2240	2240	2060
									8.7	5420	5090	5020	4930	4930	4930	4540
									0.8	2870	2690	2660	2610	2610	2610	2390
									11.6	6320	5930	5860	5750	5750	5750	5260
									1.0	3290	3080	3050	2990	2990	2990	2740
				14.5	7250	6780	6720		6590	6590	6590	6040				
				1.2	3700	3460	3430		3360	3360	3360	3080				
				17.4	8150	7620	7560		7400	7400	7400	6780				
				1.6	4520	4230	4190		4110	4110	4110	3770				
				23.2	9960	9320	9230		9050	9050	9050	8300				
2.0	4950	4640	4590	4500	4500	4500	4130									
29	10900	10220	10110	9910	9910	9910	9100									
VF 600/65R28 NRO (SB)	DW21B	DW20B	DW20B	597	1491	677	4477	163D	0.6	2730	2550	2530	2480	2480	2480	2280
									9	6010	5620	5570	5460	5460	5460	5020
									0.8	3180	2980	2950	2890	2890	2890	2650
									12	7000	6560	6500	6370	6370	6370	5840
									1.0	3640	3410	3380	3310	3310	3310	3040
				15	8020	7510	7440		7290	7290	7290	6700				
				1.2	3970	3720	3680		3610	3610	3610	3310				
				17	8740	8190	8110		7950	7950	7950	7290				
				1.6	4850	4540	4500		4410	4410	4410	4050				
				23	10680	10000	9910		9710	9710	9710	8920				
2.0	5360	5020	4970	4875	4875	4875	4470									
29	11810	11060	10950	10740	10740	10740	9850									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	mm	mm		10	25	30	40	50	65	70	
				inch	inch	inch	inch		bar	6	16	19	25	31	40	43
VF 540/65R30 NRO (SB)	DW20B	W18L,DW18L	W16L	539	1464	671	4396	161 D	0.6	2450	2300	2270	2230	2230	2230	2050
									9	5400	5070	5000	4910	4910	4910	4520
									0.8	2870	2690	2660	2610	2610	2610	2390
									12	6320	5930	5860	5750	5750	5750	5260
									1.0	3280	3070	3040	2980	2980	2980	2730
									15	7220	6760	6700	6560	6560	6560	6010
				1.2	3690	3450	3420		3350	3350	3350	3070				
				17	8130	7600	7530		7380	7380	7380	6760				
				1.6	4510	4220	4180		4100	4100	4100	3760				
				23	9930	9300	9210		9030	9030	9030	8280				
				2.0	5020	4700	4650		4560	4560	4560	4180				
				29	11060	10350	10240		10040	10040	10040	9210				
				2.4	5090	4760	4720		4625	4625	4625	4240				
				35	11210	10480	10400		10190	10190	10190	9340				
VF 600/60R30 NRO (SB)	DW20B	DW21B	DW18L	597	1482	678	4450	162D	0.6	2540	2380	2360	2310	2310	2310	2120
									8.7	5590	5240	5200	5090	5090	5090	4670
									0.8	2970	2780	2750	2700	2700	2700	2480
									11.6	6540	6120	6060	5950	5950	5950	5460
									1.0	3390	3170	3140	3080	3080	3080	2830
									14.5	7470	6980	6920	6780	6780	6780	6230
				1.2	3820	3570	3540		3470	3470	3470	3180				
				17.4	8410	7860	7800		7640	7640	7640	7000				
				1.6	4660	4370	4320		4240	4240	4240	3890				
				23.2	10260	9630	9520		9340	9340	9340	8570				
				2.0	5230	4890	4850		4750	4750	4750	4360				
				29	11520	10770	10680		10460	10460	10460	9600				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm					10	25	30	40	50	65	70
				inch	inch					6	16	19	25	31	40	43
VF 600/65R30 NRO (SB)	DW21B	-	DW20B	597	1542	703	4630	161 D	0.8	3280	3070	3040	2980	2980	2980	2730
									12	7220	6760	6700	6560	6560	6560	6010
									1.0	3750	3510	3480	3410	3410	3410	3130
				23.5	60.7	27.7	182.3		15	8260	7730	7670	7510	7510	7510	6890
									1.2	4210	3940	3910	3830	3830	3830	3510
									17	9270	8680	8610	8440	8440	8440	7730
									1.6	5090	4760	4720	4625	4625	4625	4240
23	11210	10480	10400	10190	10190	10190	9340									
VF 600/70R30 NRO (SB)	DW21B	DW20B	DW20B	603	1602	728	4811	170D	0.6	3090	2890	2870	2810	2810	2810	2580
									9	6810	6370	6320	6190	6190	6190	5680
									0.8	3610	3380	3350	3280	3280	3280	3010
									12	7950	7440	7380	7220	7220	7220	6630
									1	4130	3860	3830	3750	3750	3750	3440
									15	9100	8500	8440	8260	8260	8260	7580
				23.7	63.1	28.7	189		1.2	4640	4350	4300	4220	4220	4220	3870
									17	10220	9580	9470	9300	9300	9300	8520
									1.6	5680	5310	5260	5160	5160	5160	4730
									23	12510	11700	11590	11370	11370	11370	10420
									2	6330	5920	5870	5750	5750	5750	5280
									29	13940	13040	12930	12670	12670	12670	11630
									2	6600	6180	6120	6000	6000	6000	5500
35	14540	13610	13480	13220	13220	13220	12110									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	10	25			30	40	50	65	70		
				inch	inch	inch	inch		inch	inch	inch	inch	inch			
VF 380/85R34 (SB)	W13	W12,DW12,DW13		383	1510	698	4516	149 D	0.6	1940	1810	1800	1760	1760	1760	1610
									9	4270	3990	3960	3880	3880	3880	3550
									0.8	2260	2110	2090	2050	2050	2050	1880
									12	4980	4650	4600	4520	4520	4520	4140
									1.0	2570	2410	2390	2340	2340	2340	2150
				15	5660	5310	5260		5150	5150	5150	4740				
				1.2	2890	2710	2680		2630	2630	2630	2410				
				17	6370	5970	5900		5790	5790	5790	5310				
				1.4	3220	3020	2990		2930	2930	2930	2690				
				20	7090	6650	6590		6450	6450	6450	5930				
1.6	3580	3350	3320	3250	3250	3250	2980									
23	7890	7380	7310	7160	7160	7160	6560									
VF 420/85R34 (SB)	DW15L	DW14L		419	1578	726	4739	159 D	0.6	2230	2090	2070	2030	2030	2030	1860
									9	4910	4600	4560	4470	4470	4470	4100
									0.8	2610	2440	2420	2370	2370	2370	2170
									12	5750	5370	5330	5220	5220	5220	4780
									1.0	2980	2790	2760	2710	2710	2710	2490
				15	6560	6150	6080		5970	5970	5970	5480				
				1.2	3360	3140	3110		3050	3050	3050	2800				
				17	7400	6920	6850		6720	6720	6720	6170				
				1.6	4100	3840	3800		3730	3730	3730	3420				
				23	9030	8460	8370		8220	8220	8220	7530				
2.0	4500	4210	4170	4090	4090	4090	3750									
29	9910	9270	9190	9010	9010	9010	8260									
2.4	4810	4510	4460	4375	4375	4375	4010									
35	10590	9930	9820	9640	9640	9640	8830									
VF 600/60R34 (SB)	DW20B	DW21B		597	1584	729	4757	160 D	0.6	2700	2520	2500	2450	2450	2450	2250
									9	5950	5550	5510	5400	5400	5400	4960
									0.8	3150	2950	2920	2860	2860	2860	2620
									12	6940	6500	6430	6300	6300	6300	5770
									1.0	3600	3370	3340	3270	3270	3270	3000
				15	7930	7420	7360		7200	7200	7200	6610				
				1.2	4040	3780	3740		3670	3670	3670	3370				
				17	8900	8330	8240		8080	8080	8080	7420				
				1.4	4490	4200	4160		4080	4080	4080	3740				
				20	9890	9250	9160		8990	8990	8990	8240				
1.6	4950	4640	4590	4500	4500	4500	4130									
23	10900	10220	10110	9910	9910	9910	9100									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm					10	25	30	40	50	65	70
				inch	inch					6	16	19	25	31	40	43
VF 600/70R34 NRO (SB)	DW21B	DW20B	DW20B	603	1704	778	5117	170 D	0.6	3270	3060	3030	2970	2970	2970	2720
									9	7200	6740	6670	6540	6540	6540	5990
									0.8	3820	3570	3540	3470	3470	3470	3180
									12	8410	7860	7800	7640	7640	7640	7000
									1.0	4360	4080	4040	3960	3960	3960	3630
				15	9600	8990	8900		8720	8720	8720	8000				
				1.2	4910	4590	4550		4460	4460	4460	4090				
				17	10810	10110	10020		9820	9820	9820	9010				
				1.6	6000	5610	5560		5450	5450	5450	5000				
				23	13220	12360	12250		12000	12000	12000	11010				
2.0	6600	6180	6120	6000	6000	6000	5500									
29	14540	13610	13480	13220	13220	13220	12110									
VF 650/60R34 NRO (SB)	DW23B	DW21B	DW20B	650	1644	731	4937	168 D	0.6	3050	2850	2830	2770	2770	2770	2540
									9	6720	6280	6230	6100	6100	6100	5590
									0.8	3550	3330	3290	3230	3230	3230	2960
									12	7820	7330	7250	7110	7110	7110	6520
									1.0	4060	3800	3760	3690	3690	3690	3390
				15	8940	8370	8280		8130	8130	8130	7470				
				1.2	4570	4270	4230		4150	4150	4150	3810				
				17	10070	9410	9320		9140	9140	9140	8390				
				1.6	5590	5230	5180		5080	5080	5080	4660				
				23	12310	11520	11410		11190	11190	11190	10260				
2.0	6160	5770	5710	5600	5600	5600	5140									
29	13570	12710	12580	12330	12330	12330	11320									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	mm	mm			10	25	30	40	50	65	70
				inch	inch	inch	inch		bar	6	16	19	25	31	40	43
VF 650/65R34 NRO (SB)	DW23B	DW21B	DW20B	650	1710	781	5135	170 D	0.6	3380	3160	3130	3070	3070	3070	2820
									9	7440	6960	6890	6760	6760	6760	6210
									0.8	3940	3690	3650	3580	3580	3580	3280
									12	8680	8130	8040	7890	7890	7890	7220
									1.0	4500	4210	4170	4090	4090	4090	3750
									15	9910	9270	9190	9010	9010	9010	8260
			25.6	67.3	30.7	202.2	1.2		5060	4740	4690	4600	4600	4600	4600	4220
							17		11150	10440	10330	10130	10130	10130	9300	
							1.6		6000	5610	5560	5450	5450	5450	5000	
							23		13220	12360	12250	12000	12000	12000	11010	
							2.0		6600	6180	6120	6000	6000	6000	5500	
							29		14540	13610	13480	13220	13220	13220	12110	
VF 710/60R34 NRO (SB)	DW25B	DW24B,DW27B	DW23B	708	1716	783	5153	173 D	0.8	4070	3810	3770	3700	3700	3700	3390
									12	8960	8390	8300	8150	8150	8150	7470
									1.0	4650	4360	4310	4230	4230	4230	3880
									15	10240	9600	9490	9320	9320	9320	8550
									1.2	5240	4900	4860	4760	4760	4760	4370
									17	11540	10790	10700	10480	10480	10480	9630
			27.9	67.6	30.8	202.9	1.4		5820	5450	5400	5290	5290	5290	5290	4850
							20		12820	12000	11890	11650	11650	11650	10680	
							1.6		6400	5990	5940	5820	5820	5820	5340	
							23		14100	13190	13080	12820	12820	12820	11760	
							2.0		7150	6700	6630	6500	6500	6500	5960	
							29		15750	14760	14600	14320	14320	14320	13130	

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm					10	25	30	40	50	65	70
				inch	inch					6	16	19	25	31	40	43
VF 380/80R38 (SB)	DW12	W12	-	383	1573	733	4724	167 D	0.6	1940	1810	1800	1760	1760	1760	1610
									9	4270	3990	3960	3880	3880	3880	3550
									0.8	2270	2120	2100	2060	2060	2060	1890
									12	5000	4670	4630	4540	4540	4540	4160
									1	2590	2420	2400	2350	2350	2350	2160
									15	5700	5330	5290	5180	5180	5180	4760
									1.2	2900	2720	2690	2640	2640	2640	2420
									17	6390	5990	5930	5810	5810	5810	5330
									1.6	3550	3330	3290	3230	3230	3230	2960
									23	7820	7330	7250	7110	7110	7110	6520
				2	3890	3650	3610		3540	3540	3540	3250				
				29	8570	8040	7950		7800	7800	7800	7160				
				2.4	4160	3890	3860		3780	3780	3780	3470				
				35	9160	8570	8500		8330	8330	8330	7640				
				2.8	4550	4260	4220		4140	4140	4140	3800				
				41	10020	9380	9300		9120	9120	9120	8370				
				3.2	4910	4590	4550		4460	4460	4460	4090				
				46	10810	10110	10020		9820	9820	9820	9010				
				3.6	5240	4900	4860		4760	4760	4760	4370				
				52	11540	10790	10700		10480	10480	10480	9630				
4	5520	5170	5120	5020	5020	5020	4610									
58	12160	11390	11280	11060	11060	11060	10150									
4.4	6000	5610	5560	5450	5450	5450	5000									
64	13220	12360	12250	12000	12000	12000	11010									
VF 380/95R38 NRO (SB)	W13	W12	W12	383	1687	780	5066	159D	0.6	2220	2080	2060	2020	2020	2020	1850
									8.7	4890	4580	4540	4450	4450	4450	4070
									0.8	2600	2430	2410	2360	2360	2360	2170
									11.6	5730	5350	5310	5200	5200	5200	4780
									1	2970	2780	2750	2700	2700	2700	2480
				14.5	6540	6120	6060		5950	5950	5950	5460				
				1.2	3340	3130	3100		3040	3040	3040	2790				
				17.4	7360	6890	6830		6700	6700	6700	6150				
				1.6	4080	3820	3780		3710	3710	3710	3400				
				23.2	8990	8410	8330		8170	8170	8170	7490				
				2	4480	4190	4150		4070	4070	4070	3730				
				29	9870	9230	9140		8960	8960	8960	8220				
				2.4	4810	4510	4460		4375	4375	4375	4010				
				34.8	10590	9930	9820		9640	9640	9640	8830				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Reco mm. Rim	ALT Rim	NR O	Unloaded Dimension		Stati c Load Radius	Rolling Circum.	LI/S I	Inflat ion Pressure	Recommend load (kg) (lbs)							
				SW	OD					Speed (kmph) (mph)							
				mm	mm					10	25	30	40	50	65	70	
				inch	inch					bar	psi	6	16	19	25	31	40
VF 420/85R38 (SB)	DW15L	DW14L	.	429	1679	777	5022	155 D	0.6	2350	2200	2180	2140	2140	2140	1960	
									9	5180	4850	4800	4710	4710	4710	4320	
									0.8	2750	2580	2550	2500	2500	2500	2290	
									12	6060	5680	5620	5510	5510	5510	5040	
									1.0	3150	2950	2920	2860	2860	2860	2620	
									15	6940	6500	6430	6300	6300	6300	5770	
				1.2	3540	3320	3280		3220	3220	3220	2950					
				17	7800	7310	7220		7090	7090	7090	6500					
				1.4	3930	3680	3640		3570	3570	3570	3280					
				20	8660	8110	8020		7860	7860	7860	7220					
				1.6	4260	3990	3950		3875	3875	3875	3560					
				23	9380	8790	8700		8540	8540	8540	7840					
VF 650/65R38 (SB)	DW23B	DW21B	.	650	1811	831	5438	180 D	0.6	3540	3320	3280	3220	3220	3220	2950	
									8.7	7800	7310	7220	7090	7090	7090	6500	
									0.8	4140	3870	3840	3760	3760	3760	3450	
									11.6	9120	8520	8460	8280	8280	8280	7600	
									1.0	4730	4430	4390	4300	4300	4300	3940	
									14.5	10420	9760	9670	9470	9470	9470	8680	
									1.2	5160	4830	4780	4690	4690	4690	4300	
									17.4	11370	10640	10530	10330	10330	10330	9470	
									1.6	6300	5900	5840	5730	5730	5730	5260	
				23.2	13880	13000	12860		12620	12620	12620	11590					
				2	7010	6560	6500		6370	6370	6370	5840					
				29	15440	14450	14320		14030	14030	14030	12860					
				2.4	7560	7080	7010		6870	6870	6870	6300					
				34.8	16650	15590	15440		15130	15130	15130	13880					
				2.8	8270	7750	7670		7520	7520	7520	6900					
				40.6	18220	17070	16890		16560	16560	16560	15200					
				3.2	8800	8240	8160		8000	8000	8000	7340					
				46.4	19380	18150	17970		17620	17620	17620	16170					
25.6	71.3	32.7	214.1														

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm					10	25	30	40	50	65	70
				inch	inch					6	16	19	25	31	40	43
VF 710/60R38 NRO (SB)	DW25B	DW24B,DW27B	DW23B	708	1817	834	5456	174D	0.6	3670	3440	3410	3340	3340	3340	3060
									9	8080	7580	7510	7360	7360	7360	6740
									0.8	4280	4010	3970	3890	3890	3890	3570
									12	9430	8830	8740	8570	8570	8570	7860
									1	4900	4580	4540	4450	4450	4450	4080
				15	10790	10090	10000		9800	9800	9800	8990				
				1.2	5510	5160	5110		5010	5010	5010	4600				
				17	12140	11370	11260		11040	11040	11040	10130				
				1.6	6730	6300	6240		6120	6120	6120	5610				
				23	14820	13880	13740		13480	13480	13480	12360				
VF 710/70R38 NRO (SB)	DW25B	DW24B,DW23B	DW23B	705	1959	893	5883	181D	0.6	4280	4010	3970	3890	3890	3890	3570
									8.7	9430	8830	8740	8570	8570	8570	7860
									0.8	4990	4680	4630	4540	4540	4540	4170
									11.6	10990	10310	10200	10000	10000	10000	9190
									1	5700	5340	5280	5180	5180	5180	4750
				14.5	12560	11760	11630		11410	11410	11410	10460				
				1.2	6410	6000	5950		5830	5830	5830	5350				
				17.4	14120	13220	13110		12840	12840	12840	11780				
				1.6	7840	7340	7270		7130	7130	7130	6540				
				23.2	17270	16170	16010		15700	15700	15700	14410				
2	9080	8500	8420	8250	8250	8250	7570									
29	20000	18720	18550	18170	18170	18170	16670									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	10	25			30	40	50	65	70		
				inch	inch	6	16			19	25	31	40	43		
VF 800/70R38 NRO (SB)	DW28B	DW25B, DW27B, DW30B	DW27B	804	2085	945	6261	187D	0.6	5380	5040	4990	4890	4890	4890	4490
									9	11850	11100	10990	10770	10770	10770	9890
									0.8	6280	5880	5820	5710	5710	5710	5240
									12	13830	12950	12820	12580	12580	12580	11540
									1	7170	6720	6650	6520	6520	6520	5980
									15	15790	14800	14650	14360	14360	14360	13170
				1.2	8070	7560	7490		7340	7340	7340	6730				
				17	17780	16650	16500		16170	16170	16170	14820				
				1.6	9870	9240	9150		8970	8970	8970	8230				
				23	21740	20350	20150		19760	19760	19760	18130				
				2	10730	10040	9950		9750	9750	9750	8940				
				29	23630	22110	21920		21480	21480	21480	19690				
VF 650/65R42 NRO (SB)	DW23B	DW21B	DW20B	650	1913	882	5745	174D	0.6	3720	3480	3450	3380	3380	3380	3100
									9	8190	7670	7600	7440	7440	7440	6830
									0.8	4330	4060	4020	3940	3940	3940	3610
									12	9540	8940	8850	8680	8680	8680	7950
									1	4960	4650	4600	4510	4510	4510	4140
									15	10930	10240	10130	9930	9930	9930	9120
				1.2	5410	5070	5020		4920	4920	4920	4510				
				17	11920	11170	11060		10840	10840	10840	9930				
				1.6	6610	6190	6130		6010	6010	6010	5510				
				23	14560	13630	13500		13240	13240	13240	12140				
				2	7370	6900	6830		6700	6700	6700	6150				
				29	16230	15200	15040		14760	14760	14760	13550				
VF 710/60R42 NRO (SB)	DW25B	DW24B, DW27B	DW23B	708	1919	885	5763	176D	0.6	3850	3610	3570	3500	3500	3500	3210
									9	8480	7950	7860	7710	7710	7710	7070
									0.8	4490	4200	4160	4080	4080	4080	3740
									12	9890	9250	9160	8990	8990	8990	8240
									1	5140	4810	4760	4670	4670	4670	4280
									15	11320	10590	10480	10290	10290	10290	9430
				1.2	5780	5410	5360		5250	5250	5250	4820				
				17	12730	11920	11810		11560	11560	11560	10620				
				1.6	7060	6610	6550		6420	6420	6420	5890				
				23	15550	14560	14430		14140	14140	14140	12970				
				2.0	7810	7310	7240		7100	7100	7100	6510				
				29	17200	16100	15950		15640	15640	15640	14340				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	10	25		30	40	50	65	70			
				inch	inch	bar	psi		6	16	19	25	31	40	43	
VF 710/70R42 NRO (SB)	DW25B	DW24B,DW23B	DW23B	705	2061	944	6189	185 D	0.6	4660	4370	4320	4240	4240	4240	3890
									9	10260	9630	9520	9340	9340	9340	8570
									0.8	5450	5100	5050	4950	4950	4950	4540
									12	12000	11230	11120	10900	10900	10900	10000
									1.0	6230	5830	5770	5660	5660	5660	5190
									15	13720	12840	12710	12470	12470	12470	11430
									1.2	7000	6550	6490	6360	6360	6360	5830
				17	15420	14430	14300		14010	14010	14010	12840				
				1.6	8560	8010	7940		7780	7780	7780	7140				
				23	18850	17640	17490		17140	17140	17140	15730				
				2.0	9390	8800	8710		8540	8540	8540	7830				
				29	20680	19380	19190		18810	18810	18810	17250				
				2.4	10180	9530	9440		9250	9250	9250	8490				
				35	22420	20990	20790		20370	20370	20370	18700				
VF 900/60R42 NRO (SB)	DW30B	-	DW28B	881	2147	979	6421	189 D	0.6	5540	5190	5140	5040	5040	5040	4620
									9	12200	11430	11320	11100	11100	11100	10180
									0.8	6470	6060	6000	5880	5880	5880	5390
									12	14250	13350	13220	12950	12950	12950	11870
									1.0	7390	6920	6850	6720	6720	6720	6170
									15	16280	15240	15090	14800	14800	14800	13590
									1.2	8320	7790	7710	7560	7560	7560	6940
				17	18330	17160	16980		16650	16650	16650	15290				
				1.6	10160	9520	9420		9240	9240	9240	8480				
				23	22380	20970	20750		20350	20350	20350	18680				
				2.0	11330	10610	10510		10300	10300	10300	9450				
				29	24960	23370	23150		22690	22690	22690	20810				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	10	25			30	40	50	65	70		
				inch	inch	inch	inch		inch	inch	inch	inch	inch			
VF 750/70R44 (SB)	DW25B			742	2168	992	6484	186 D	0.6	5190	4860	4810	4720	4720	4720	4330
									9	11430	10700	10590	10400	10400	10400	9540
									0.8	6050	5670	5610	5500	5500	5500	5050
									12	13330	12490	12360	12110	12110	12110	11120
									1.0	6920	6480	6420	6290	6290	6290	5770
									15	15240	14270	14140	13850	13850	13850	12710
				1.2	7790	7290	7220		7080	7080	7080	6500				
				17	17160	16060	15900		15590	15590	15590	14320				
				1.6	9520	8910	8820		8650	8650	8650	7940				
				23	20970	19630	19430		19050	19050	19050	17490				
				2.0	10450	9790	9690		9500	9500	9500	8720				
				29	23020	21560	21340		20930	20930	20930	19210				
VF 380/85R46 NRO (SB)	W13	DW12,W12,DW13	W12	383	1814	851	5447	162 D	0.6	2240	2100	2080	2040	2040	2040	1870
									9	4930	4630	4580	4490	4490	4490	4120
									0.8	2620	2450	2430	2380	2380	2380	2180
									12	5770	5400	5350	5240	5240	5240	4800
									1	2990	2800	2770	2720	2720	2720	2500
									15	6590	6170	6100	5990	5990	5990	5510
									1.2	3370	3150	3120	3060	3060	3060	2810
									17	7420	6940	6870	6740	6740	6740	6190
				1.6	4110	3850	3810		3740	3740	3740	3430				
				23	9050	8480	8390		8240	8240	8240	7560				
				2	4520	4230	4190		4110	4110	4110	3770				
				29	9960	9320	9230		9050	9050	9050	8300				
				2.4	4820	4510	4470		4380	4380	4380	4020				
				35	10620	9930	9850		9650	9650	9650	8850				
				2.8	5230	4890	4850		4750	4750	4750	4360				
				41	11520	10770	10680		10460	10460	10460	9600				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	NRO	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)						
				SW	OD					Speed (kmph) (mph)						
				mm	mm	10	25			30	40	50	65	70		
				inch	inch	inch	inch			inch	inch	inch	inch	inch		
VF 480/80R46 (SB)	DW16L	DW15L	.	479	1936	901	5814	177D	0.6	3010	2820	2790	2740	2740	2740	2510
									9	6630	6210	6150	6040	6040	6040	5530
									0.8	3510	3290	3250	3190	3190	3190	2930
									12	7730	7250	7160	7030	7030	7030	6450
									1.0	4020	3760	3720	3650	3650	3650	3350
									15	8850	8280	8190	8040	8040	8040	7380
									1.2	4520	4230	4190	4110	4110	4110	3770
				17	9960	9320	9230		9050	9050	9050	8300				
				1.6	5520	5170	5120		5020	5020	5020	4610				
				23	12160	11390	11280		11060	11060	11060	10150				
				2.0	6060	5680	5620		5510	5510	5510	5060				
				29	13350	12510	12380		12140	12140	12140	11150				
				2.4	6450	6040	5980		5860	5860	5860	5380				
				35	14210	13300	13170		12910	12910	12910	11850				
				2.8	7070	6620	6560		6430	6430	6430	5900				
				41	15570	14580	14450		14160	14160	14160	13000				
				3.2	7620	7140	7070		6930	6930	6930	6360				
46	16780	15730	15570	15260	15260	15260	14010									
3.6	8030	7520	7450	7300	7300	7300	6700									
52	17690	16560	16410	16080	16080	16080	14760									
VF 480/95R54 NRO (SB)	DW16L	DW15L	DW15L	479	2284	1062	6859	180 D	0.6	3760	3520	3490	3420	3420	3420	3140
									9	8280	7750	7690	7530	7530	7530	6920
									0.8	4400	4120	4080	4000	4000	4000	3670
									12	9690	9070	8990	8810	8810	8810	8080
									1.0	5030	4710	4660	4570	4570	4570	4190
									15	11080	10370	10260	10070	10070	10070	9230
									1.2	5650	5290	5240	5140	5140	5140	4720
				17	12440	11650	11540		11320	11320	11320	10400				
				1.6	6910	6470	6410		6280	6280	6280	5760				
				23	15220	14250	14120		13830	13830	13830	12690				
				2.0	7580	7100	7030		6890	6890	6890	6320				
				29	16700	15640	15480		15180	15180	15180	13920				
				2.4	8070	7560	7490		7340	7340	7340	6730				
				35	17780	16650	16500		16170	16170	16170	14820				
				2.8	8800	8240	8160		8000	8000	8000	7340				
				41	19380	18150	17970		17620	17620	17620	16170				

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)							
			SW	OD					Speed (kmph) (mph)							
			mm	mm					Harvester Application				CFO			
			inch	inch					10	25	30	40	50	Upto 15 Cyc.	Upto 30 Cyc.	
VF 600/65R28 CFO (SB)	DW20B	DW21B	597	1491	677	4477	166A8	0.6	2510	2350	2330	2480	2280	3360	2810	
								9	5530	5180	5130	5460	5020	7400	6190	
								0.8	2920	2730	2700	2890	2650	3920	3280	
								12	6430	6010	5950	6370	5840	8630	7220	
								1	3340	3130	3100	3310	3040	4490	3760	
			15	7360	6890	6830		7290	6700	9890	8280					
			1.2	3640	3410	3380		3610	3310	4890	4100					
			17	8020	7510	7440		7950	7290	10770	9030					
			1.6	4460	4170	4130		4410	4050	5980	5010					
			23	9820	9190	9100		9710	8920	13170	11040					
VF 540/65R30 CRO (SB)	DW20B	W18L, DW18L	539	1464	671	4396	161A8	0.6	2260	2110	2090	2230	2050	3020	2530	
								8.7	4980	4650	4600	4910	4520	6650	5570	
								0.8	2630	2460	2440	2610	2390	3540	2960	
								11.6	5790	5420	5370	5750	5260	7800	6520	
								1	3000	2810	2780	2980	2730	4040	3380	
			14.5	6610	6190	6120		6560	6010	8900	7440					
			1.2	3380	3160	3130		3350	3070	4540	3800					
			17.4	7440	6960	6890		7380	6760	10000	8370					
			1.6	4600	4310	4260		4560	4180	6180	5180					
			23.2	10130	9490	9380		10040	9210	13610	11410					
VF 710/70R38 CFO (SB)	DW25B	DW24, DW23B	705	1959	893	5883	183A8	0.6	3930	3680	3640	3890	3570	5270	4420	
								8.7	8660	8110	8020	8570	7860	11610	9740	
								0.8	4590	4300	4250	4540	4170	6150	5150	
								11.6	10110	9470	9360	10000	9190	13550	11340	
								1	5230	4890	4850	5180	4750	7020	5880	
			14.5	11520	10770	10680		11410	10460	15460	12950					
			1.2	5890	5510	5460		5830	5350	7900	6620					
			17.4	12970	12140	12030		12840	11780	17400	14580					
			1.6	7190	6740	6670		7130	6540	9660	8090					
			23.2	15840	14850	14690		15700	14410	21280	17820					
2	8240	7710	7640	8160	7490	11060	9260									
29	18150	16980	16830	17970	16500	24360	20400									
2.4	8830	8270	8190	8750	8030	11860	9930									
34.8	19450	18220	18040	19270	17690	26120	21870									

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

Technical Data



Size	Recomm. Rim	ALT Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	LI/SI	Inflation Pressure	Recommend load (kg) (lbs)							
			SW	OD					Speed (kmph) (mph)							
			mm	mm					Harvester Application				CFO			
			inch	inch					10	25	30	40	50	Upto 15 Cyc.	Upto 30 Cyc.	
VF 800/70R38 CFO (SB)	DW28B	DW25B, DW27B, DW30B	804	2085	945	6261	190A8	0.6	4940	4620	4580	4890	4490	6630	5550	
								9	10880	10180	10090	10770	9890	14600	12220	
								0.8	5760	5400	5340	5710	5240	7740	6480	
								12	12690	11890	11760	12580	11540	17050	14270	
								1	6580	6160	6100	6520	5980	8830	7400	
								15	14490	13570	13440	14360	13170	19450	16300	
								1.2	7400	6930	6860	7340	6730	9950	8330	
		17	16300	15260	15110	16170		14820	21920	18350						
		1.6	9050	8480	8390	8970		8230	12150	10180						
		23	19930	18680	18480	19760		18130	26760	22420						
		2	9930	9300	9210	9840		9030	13330	11170						
		29	21870	20480	20290	21670		19890	29360	24600						
		2.4	10690	10010	9910	10600		9720	14360	12030						
		35	23550	22050	21830	23350		21410	31630	26500						
VF 710/70R42 CFO (SB)	DW25B	DW24, DW23B	705	2061	944	6189	190A8	0.6	4280	4010	3970	4240	3890	5750	4810	
								9	9430	8830	8740	9340	8570	12670	10590	
								0.8	4990	4680	4630	4950	4540	6710	5620	
								12	10990	10310	10200	10900	10000	14780	12380	
								1.0	5710	5350	5290	5660	5190	7670	6420	
								15	12580	11780	11650	12470	11430	16890	14140	
								1.2	6410	6000	5950	6360	5830	8620	7220	
		17	14120	13220	13110	14010		12840	18990	15900						
		1.6	7850	7350	7280	7780		7140	10540	8830						
		23	17290	16190	16040	17140		15730	23220	19450						
		2.0	8610	8060	7990	8540		7830	11570	9690						
		29	18960	17750	17600	18810		17250	25480	21340						
		2.4	9170	8590	8510	9090		8340	12320	10320						
		35	20200	18920	18740	20020		18370	27140	22730						
2.8	10050	9410	9320	9960	9140	13500	11300									
41	22140	20730	20530	21940	20130	29740	24890									
3.2	10690	10010	9910	10600	9720	14360	12030									
46	23550	22050	21830	23350	21410	31630	26500									

Note: VF- Very High Flexion, SB - Steel Belted, SG- Stubble Guard, CFO - Cyclical Field Operation, NRO - Narrow Rim Option

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com